



### **Product Highlights:**

- 9.5x faster than hard disk drives with up to
  1050MB/s read and 1000MB/s write<sup>1</sup>, for significantly
  faster transfers
- Super-fast backups and instant storage expansion
- Built-in, double-layer graphite sheets quickly conduct heat, enhancing heat dissipation to keep the drive cool, even during blazing-fast transfers
- The drive is drop-resistant up to 2 meters for protection, ensuring durability for everyday and office use
- Plug-and-play compatibility with a 2-in-1
  USB-C/USB-A cable to easily use with your PC, Mac®,
  tablet, smartphone, and more
- Includes Lexar® DataShield™ 256-bit AES encryption software to protect files and access to the Lexar Recovery Tool³ to help restore accidentally deleted

#### Capacities:

**1T**B **2**TB



# Super-fast Backups for Superior Efficiency

The Lexar® ES3 Portable SSD unleashes incredible performance with 1050MB/s read and 1000MB/s¹ write speeds clocking in at 9.5x faster than HDDs.¹

**9.5x Faster than Standard Hard Drives.** With up to 1050MB/s read and 1000MB/s¹ write, the Portable SSD delivers significantly faster transfers for better productivity.

**Super-fast Backups.** Say goodbye to storage woes and hello to seamless, high-speed backups and instant storage expansion.

**Enhanced Heat Dissipation.** Built-in, double-layer graphite sheets quickly conduct heat, keeping the drive cool, even during heavy usage and blazing-fast transfers..

**Drop-Resistant.** With its durable design, this drive is as sturdy as it is sleek, featuring an impressive fall protection up to 2 meters.

**Extensive Compatibility.** A 2-in-1 USB-C/USB-A cable ensures that the drive is compatible with your PC, Mac, tablet, smartphone, and more.

**Safeguard Your Files.** Includes Lexar® DataShield™ 256-bit AES encryption software to help protect your files and access to the Lexar Recovery Tool³ to help restore accidentally deleted files.

**Rigorously Tested.** All Lexar products undergo extensive testing in the Lexar Quality Labs, facilities with thousands of different cameras and digital devices to ensure performance, quality, compatibility, and reliability.

For more than 28 years, Lexar has been trusted as a leading global brand of memory solutions. Our award-winning lineup includes memory cards, USB flash drives, card readers, solid-state drives, and DRAM. With so many options, it's easy to find the right Lexar solution to fit your needs. Lexar products are available worldwide at major retail and e-tail stores. For more information or support, visit <a href="https://www.lexar.com">www.lexar.com</a>.

Lexar is not liable for any loss of data or images

Product appearance, performance, software offerings, and packaging may vary depending on ship date and available inventory Actual usable memory capacity may vary. 1GB equals 1 billion bytes.

## www.lexar.com

©2024 All Rights Reserved. Information, products, specifications, and features are subject to change without notice. Neither Lexar nor Longsys is responsible for omissions or errors in typography or photography. Lexar, the Lexar logo, and all other Lexar trademarks are the property of Longsys Electronics (HK) Co., Ltd. or Shenzhen Longsys Electronics Co., Ltd. All other trademarks are property of their respective owners.

Lexar-ProductSheet-ES3-EN 09/2024

Speeds based on internal testing. Actual speed may vary depending on host device.

<sup>&</sup>lt;sup>2</sup> 2-meter anti-drop based on internal testing conducted under controlled conditions. Actual drop resistance capabilities may vary. Damage caused by drops is not covered under warranty.

 $<sup>^{\</sup>rm 3}$  Please note that the data recovery rate may not be 100%.



Lexar Retail SKU	Capacity	Region	Single UPC Code	Inner Carton UPC Code	Inner Carton Qty
LES3XXX001T-RNSNG	1TB	Global	843367137992	10843367137999	- 10
LES3XXX002T-RNSNG	2TB		843367138005	10843367138002	

# **Specifications**

Capacity	1TB / 2TB		
Interface	USB 3.2 Gen 2		
Speed	Up to 1050MB/s read, up to 1000MB/s write <sup>1</sup>		
Operating Temperature	0°C to 50°C (32°F to 122°F)		
Storage Temperature	-40°C to 85°C (-40°F to 185°F)		
Size (L x W x H)	100.6mm x 50mm x 10.5mm		
Weight	45g		
Warranty	3-year limited warranty		

www.lexar.com

©2024 All Rights Reserved. Information, products, specifications, and features are subject to change without notice. Neither Lexar nor Longsys is responsible for omissions or errors in typography or photography. Lexar, the Lexar logo, and all other Lexar trademarks are the property of Longsys Electronics (HK) Co., Ltd. or Shenzhen Longsys Electronics Co., Ltd. All other trademarks are property of their respective owners.

Lexar-ProductSheet-ES3-EN 09/2024